

## **Bunded Lube Skids & Trailers**


The *Cashels* range of **Bunded Lube Skids & Trailers** has been developed for servicing mobile equipment in the construction, mining and various other on-site environments. They are also used by companies who service large installations of compressors and standby generators in data centres, treatment plants, communication towers and generator stations etc.





**Bunded Lube Trailers** are offered in numerous configurations to suit customer requirements. Typical configurations are 2-4 internal lube tanks, complete with 12/24v lube pumps and self retracting hose reels. *Cashels* unique modular design incorporates a separate outer tank with a removable roof to allow access to the internal lube tanks and equipment. The separate outer tank also acts as the bund tank and has 110% capacity of the internal lube tanks.





## Key Features:

- Modular construction with secure storage for all equipment.
- Pneumatic or 12/24v DC lube pumps available.
- Outer bund holds in excess of 110% of total volume.
- Air manifold to allow complete control of each pump system (pneumatic models).

Model	Length	Width	Max Height	Unladen Weight	Max Gross Weight	Waste Oil Tank Vol.	New Oil Tank Vol.
3 Tank	1506mm <i>(59″)</i>	1500mm <i>(59″)</i>	1286mm <i>(51″)</i>	770kg (1694lbs)	1220kg (2684lbs)	330L (72gal)	2x 160L (2x 35gal)
4 Tank	1490mm <i>(59″)</i>	1974mm <i>(78″)</i>	1286mm <i>(51″)</i>	870kg (1914lbs)	1430kg <i>(3146lbs)</i>	330L (72gal)	3x 110L (3x 24gal)
Trailer	3687mm <i>(145″)</i>	1921mm <i>(76″)</i>	1975mm <i>(77″)</i>	1340kg (2948lbs)	2831kg (6228lbs)	Model specific	Model specific

We reserve the right to alter designs & specifications without notice. Copyright © Cashels Engineering Ltd. 2020