

Bunded High-Speed Fuel Bowers



Feature	220G (1000L) High Speed Bunded	400G (1818L) High Speed Bunded	220G (1000L) Static Trans Bunded	400G (1818L) Static Trans Bunded
Length (mm)	2980	3240	2015	2015
Width (mm)	1830	1940	1585	1720
Height (mm)	1560	1940	1170	1522
Weight, Unladen (kg)	940	1210	785	1015
Weight, Laden (kg)	1760	2705	1605	2510
Wheel Specification	165RI3C 8-Ply	165R13C 8-Ply	-	-
Rubber compression axle/suspension,braked hubs	Twin, Braked Suspension	Twin, Braked Suspension	-	-
Auto-reverse, braked hitch coupling	✓	✓	-	-
Jockey wheel	✓	✓	-	-
Lighting system to EU regulations	✓	✓	-	-
4mm steel container, baffled & pressure tested	✓	✓	✓	✓
Hot-dip galvanised chassis	✓	✓	-	-
Galvanised mudguards	✓	✓	-	-
PPV Valve (Pressure Relief)	✓	✓	✓	✓
12v, 55l/min pump & 3-digit flow meter	✓	✓	✓	✓
6m of ¾" fuel hose	✓	✓	✓	✓
Dipstick	✓	✓	✓	✓
Corporate colours available	✓	✓	✓	✓