

## Single Skin High-Speed Fuel Bowsers

The **Cashels** range of **Single Skin Highspeed Fuel Bowsers** has been designed and manufactured for the safe storage and legal transportation of fuels.







220G Single Skin (High-Speed)

300G Single Skin (High-Speed)

400G Single Skin (High-Speed)

All models are UN-approved to comply with the International Carriage of Dangerous Goods regulations (ADR).

The ADR-certified intermediate bulk container (IBC) i.e. the storage tank, is manufactured from 4mm mild steel and is pressure tested to ensure tank integrity.

The diesel fuelling system is securely contained within a cabinet at the front of the unit and consists of a 12-volt DC fuel pump (55lpm flow rate), 4-digit flow meter and 6 metres of delivery hose fitted with a standard nozzle.

On top of the unit, underneath a hinged, lockable hatch there is a filling point, pressure relief valve and dipstick. This top hatch can also be completely removed to allow periodic inspection of the inside of the bowser.

Feature	220G (1000ltr)	300G (1360ltr)	400G (1800ltr)
Length (mm)	2850	3945	3275
Width (mm)	1680	1842	1782
Height (mm)	1370	1430	1545
Weight Unladen (kg)	575	710	800
Weight Laden (kg)	1395	1828	2291
Wheel Specification	185R14C 8-ply	165R13C 8-ply	185R14C 8-ply
Rubber Compression Axle/Suspension, Braked Hubs	Single, Braked Suspension	Twin, Braked Suspension	Twin, Braked Suspension
Auto-Reverse, Braked Hitch Coupling	✓	✓	✓
Jockey Wheel	<b>√</b>	<b>√</b>	<b>√</b>
Lighting System to EU Approval	<b>√</b>	<b>√</b>	<b>✓</b>