

CASHELS Quality Products

www.cashels.net

Bunded Fuel Bowsers

The **Cashels** range of **Bunded Highspeed & Static Transportable Fuel Bowsers** has been designed and manufactured for the safe storage and legal transportation of fuels.



220G Bunded (Static Trans)



220G Bunded (High-Speed)



400G Bunded (High-Speed)

All models are UN-approved to comply with the International Carriage of Dangerous Goods regulations (ADR) and 110% Bunded to comply with Environmental Protection regulations.

The ADR-certified intermediate bulk container (IBC) i.e. the storage tank, is manufactured from 4mm mild steel and is pressure tested to ensure tank integrity. The IBC is then surrounded by a bund i.e. secondary containment to prevent any spillage in the unlikely event of the IBC leaking.

The diesel fuelling system is securely contained at the front of the unit and consists of a 12-volt DC fuel pump (55lpm flow rate), 3-digit flow meter and 6 metres of delivery hose fitted with a standard nozzle.

On top of the unit, underneath a hinged, lockable hatch there is a pressure relief valve and dipstick. This top hatch can also be completely removed to allow periodic inspection of the inside of the bower.

Feature	220G (1000ltr) Highspeed	400G (1800ltr) Highspeed	220G (1000ltr) Static Trans.	400G (1800ltr) Static Trans.
Length (mm)	2945	3214	2015	2015
Width (mm)	1842	1921	1585	1720
Height (mm)	1570	1962	1170	1522
Weight Unladen (kg)	912	1230	785	1015
Weight Laden (kg)	1732	2721	1605	2510
Wheel Specification	165R13C 8-ply	185R14C 8-ply	-	-
Rubber Compression Axle/Suspension, Braked Hubs	Single, Braked Suspension	Twin, Braked Suspension	-	-
Auto-Reverse, Braked Hitch Coupling	✓	✓	-	-
Jockey Wheel	✓	✓	-	-
Lighting System to EU Approval	✓	✓	-	-