

## Combi-Fuel Bowser

The *Cashels* range of **Combi-Fuel Bowsers** has been designed and manufactured for the safe storage and legal transportation of Diesel fuel and AdBlue/DEF fuel additive (UN. 1202).



**1000L Bunded Combi (High-Speed) (Front)**



**1000L Bunded Combi (High-Speed) (Rear)**

All models are UN-approved to comply with the International Carriage of Dangerous Goods regulations (ADR) and 110% Bunded to comply with Environmental Protection regulations. The chassis-mounted Bunded Fuel Bowsers also have EC Whole Vehicle Type Approval (ECWVTA). The ADR-certified diesel tanks are manufactured from 4mm mild steel, while the AdBlue tanks are manufactured from 2.5mm stainless steel.

The diesel fueling system is securely contained within the bund area at the rear of the unit and consists of a 12v DC fuel pump (55lpm flow-rate), 3-digit flow meter and 6m of delivery hose fitted with a standard nozzle. A fire extinguisher is also fitted within the bund area.

The stainless steel AdBlue tank is securely contained within a mild steel cabinet and is mounted at the front of the unit. The fuelling system comprises of a 12v DC AdBlue pump (40lpm flow-rate), inline flow meter, AdBlue delivery hose and nozzle.

See video on [www.cashels.net](http://www.cashels.net)

	<b>1000L (220gal) Combi</b>	<b>1800L (400gal) Combi</b>
<b>Length</b>	3344mm (132")	3687mm (145")
<b>Width</b>	1842mm (73")	1921mm (76")
<b>Height</b>	1570mm (62")	1975mm (78")
<b>Weight (Unladen)</b>	1010kg (2222lbs)	1340kg (2948lbs)
<b>Weight (Laden)</b>	1830kg (4026lbs)	2831kg (6228lbs)
<b>Capacity (Diesel + AdBlue/DEF)</b>	1000L + 110L (220gal + 24gal)	1800L + 150L (400gal + 33gal)
<b>Wheel Specification</b>	165R13C 8-Ply	185R14C 8-Ply
<b>Rubber Compression Axle/Suspension Braked Hubs</b>	Twin, Braked Suspension	Twin, Braked Suspension
<b>Auto-Reverse, Braked Hitch Coupling</b>	✓	✓
<b>Jockey Wheel</b>	✓	✓