

Single Skin High-Speed Fuel Bowser

The *Cashels* range of **Single Skin High-Speed Fuel Bowsers** has been designed and manufactured for the safe storage and legal transportation of fuels (UN. 1202).



1000L Single Skin (High-Speed)



1360L Single Skin (High-Speed)



1800L Single Skin (High-Speed)

All models are UN-approved to comply with the International Carriage of Dangerous Goods regulations (ADR). All Single Skin Fuel Bowsers also have EC Whole Vehicle Type Approval (ECWVTA).

The ADR-certified intermediate bulk container (IBC) i.e. the storage tank, is manufactured from 4mm mild steel and is pressure tested to ensure tank integrity.

The diesel fueling system is securely contained within a cabinet at the front of the unit and consists of a 12v DC fuel pump (55lpm flow-rate), 3-digit flow meter and 6m of delivery hose fitted with a standard nozzle.

On top of the unit, underneath a hinged, lockable hatch there is a filling point, pressure relief valve and dipstick. This top hatch can also be completely removed to allow periodic inspection of the inside of the bowser.

See video on www.cashels.net

	1000L (220gal)	1360L (300gal)	1800L (400gal)
Length	2845mm (112")	2945mm (116")	3275mm (129")
Width	1682mm (66")	1842mm (73")	1782mm (70")
Height	1370mm (54")	1430mm (56")	1545mm (61")
Weight (Unladen)	575kg (1265lbs)	710kg (1562lbs)	800kg (1760lbs)
Weight (Laden)	1395kg (3069lbs)	1828kg (4022lbs)	2291kg (5040lbs)
Wheel Specification	185R14C 8-Ply	165R13C 8-Ply	185R14C 8-Ply
Rubber Compression Axle/Suspension Braked Hubs	Single, Braked Suspension	Twin, Braked Suspension	Twin, Braked Suspension
Auto-Reverse, Braked Hitch Coupling	✓	✓	✓
Jockey Wheel	✓	✓	✓